

Péto  
**Baraka**  
LUBRIFIANT



# BARAKA TRANS HI ATF



Huile Transmissions 

## PERFORMANCE

DEXRON IIIH  
FORD MERCON V  
ALLISON C4

## HOMOLOGATION

MB-APPROVAL 236.9  
DTRF 13C170



FLUIDE  
DE TYPE  
ATF

”حكاية ثقة..”

# BARAKA TRANS

HI ATF

Automatic  
Transmission Fluid

HUILE PREMIUM



## DESCRIPTION

**Automatic Transmission Fluid (ATF)** suitable for all systems requiring DEXRON or MERCON specifications. It is particularly recommended for automatic transmissions from:

American manufacturers: GM, FORD, CHRYSLER

Asian manufacturers: HYUNDAI, KIA, MITSUBISHI, TOYOTA

European manufacturers: BMW, CITROËN, FIAT, MERCEDES, PEUGEOT, RENAULT

Also suitable for older-generation automatic transmissions, torque converters, power steering systems, marine reversing gear systems, hydrostatic transmissions, hydraulic or mechanical systems where DEXRON or MERCON specifications are required

## CLIENT BENEFITS

- Excellent thermal and oxidation stability, preventing deposit formation
- Effective protection against wear and corrosion
- Good low-temperature flow and reliable lubricant film at high operating temperatures
- Superior friction performance

### PERFORMANCE STANDARDS

- DEXRON IIIH
- FORD MERCON V
- ALLISON C4

### OEM APPROVALS

- MB-Approval 236.9 DTFR 13C170

# BARAKA TRANS

HI ATF

Automatic  
Transmission Fluid

HUILE PREMIUM



RECOMMENDED

Allison TES 295 • BMW 7045 E • BMW 8072 B • BMW LA 2634 • BMW LT 71141 • Caterpillar TO-2  
Chrysler ATF +3 • JWS 3309 (Aisin Warner) • MAN 339 Typ V1 • MAN 339 Typ Z1 • MAN 339 Typ Z2  
MB (Mercedes-Benz) 236.2 • 236.5 • 236.6 • 236.7 • 236.10 • 236.11 • 236.91 • Subaru ATF • Voith H55.6335  
Volvo 97340 • Volvo 97341 • ZF TE-ML 03D • TE-ML 04D • TE-ML 05L • TE-ML 09 • TE-ML 14A • TE-ML 14B  
TE-ML 17C • Honda ATF Z1 (sauf CVT) • Hyundai SP-II, SP-III • JASO 1-A • Mazda ATF M-III, M-V • Mitsubishi SP-II  
SP-III • Nissan AT-Matic D Fluid • AT-Matic J Fluid • Toyota Type T-II • Type T-IV

## TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Name	Units	Résultats
Density at 15 °C	-	0,866
Viscosity at 100 °C	mm <sup>2</sup> /s	7.3
Viscosity at 40 °C	mm <sup>2</sup> /s	36
Viscosity Index	-	173
Flash Point	°C	208
Pour Point	°C	-45

## STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

**Pétro  
Baraka**

   **PétroBaraka**  
[www.petrobaraka.com](http://www.petrobaraka.com)  
contact@petrobaraka.com



**رمز الثقة**  
**SYMBOLE DE CONFIANCE**  
منتج وموزع من طرف شركة ذ م م بيترو بركة  
Oued zmor, la route nationale n46 Lot n01, Biskra  
+213 (0) 33 55 27 11, 12