

BARAKA GLACIOL

TYPE **G12**

LIQUIDE DE **سائل التبريد**
REFROIDISSEMENT

خاص بجهاز التبريد **SPÉCIAL RADIATEUR**

-26°C **COOLANT**

DESCRIPTION

BARAKA GLACIOL -26° is an organic coolant based on ethylene glycol, providing freeze protection down to -26°C.

Free from harmful chemicals, it protects against corrosion and ensures stable and reliable performance in cold climatic conditions.

APPLICATION

Automotive engines: Suitable for all types of engines, including high-performance engines.

Heavy-duty vehicles: Ideal for trucks, buses, and construction vehicles.

Industrial systems: Effective for industrial cooling systems requiring long-term protection.

Maintenance: Follow manufacturer recommendations regarding mixing ratios and coolant replacement intervals.

Extreme conditions: Provides optimal protection against extreme temperatures, both freezing and boiling conditions.

FREEZING TEMPERATURE

FREEZING TEMPERATURE Up to -26 °C ❄️

CLIENT BENEFITS

- Suitable for year-round use, providing effective freeze protection
- Approved by all major European vehicle manufacturers
- Recommended for all cooling systems of internal combustion engines

BARAKA GLACIOL

TYPE G12




LIQUIDE DE **سائل التبريد**
REFROIDISSEMENT

خاص بجهاز التبريد **SPÉCIAL RADIATEUR**

-26°C **COOLANT**

TYPICAL CHARACTERISTICS

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Characteristics	Method	Unit	Typical Value
Appearance	 Visual	-	CLEAR HOMOGENEOUS
Color	 Visual	-	ORANGE
Odor	 Olfactory	-	MILD, CHARACTERISTIC
Density	ASTM D 1122	-	1063.7
pH	ASTM D 1287	-	7.8
Freezing point	ASTM D 1177	°C	-26
Boiling point	ASTM D 1120	°C	108.4
Reserve alcalinité	ASTM D1121		21.7

CONDITIONS DE STOCKAGE

This Glaciol coolant should be stored in a dry, well-ventilated area at a temperature between 5 °C and 30 °C, protected from direct sunlight.

Use properly sealed original containers and wear appropriate protective equipment during handling. A Safety Data Sheet (SDS) is available from the sales representative.

**Pétro
Baraka** 

   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12