

BARAKA GLACIOL

LIQUIDE DE **سائل التبريد**
REFROIDISSEMENT

خاص بجهاز التبريد **SPÉCIAL RADIATEUR**

-5°C **COOLANT**
UNIVERSEL

DESCRIPTION

BARAKA GLACIOL -5°C is an organic coolant with a universal formulation.

This organic coolant is based on ethylene glycol and is phosphate-free, nitrite-free, amine-free, and borate-free, ensuring long-lasting protection and broad compatibility with modern cooling systems.

APPLICATION

Automotive engines: Suitable for all types of engines, including high-performance engines.

Heavy-duty vehicles: Ideal for trucks, buses, and construction vehicles.

Industrial systems: Effective for industrial cooling systems requiring long-term protection.

Maintenance: Follow manufacturer recommendations regarding mixing ratios and coolant replacement intervals.

Extreme conditions: Provides optimal protection against extreme temperatures, both freezing and boiling conditions.

FREEZING TEMPERATURE

FREEZING TEMPERATURE Up to -5 °C 

CLIENT BENEFITS

- Corrosion protection, including for non-ferrous metals
- Protection against freezing and boiling
- Compatible with all engine types and with all Type C and Type D coolants
- Approved by all major European manufacturers
- Environmentally friendly
- Compatible with a wide range of cooling systems
- High cooling performance

BARAKA GLACIOL




LIQUIDE DE **سائل التبريد**
REFROIDISSEMENT

خاص بجهاز التبريد **SPÉCIAL RADIATEUR**

-5°C **COOLANT**
UNIVERSEL

TYPICAL CHARACTERISTICS

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Characteristics	Method	Unit	Typical Value
Appearance	 Visual	-	CLEAR HOMOGENEOUS
Color	 Visual	-	GREEN
Odor	 Olfactory	-	MILD, CHARACTERISTIC
Density	ASTM D 1122	-	1.005
pH	ASTM D 1287	-	8.00
Freezing point	ASTM D 1177	°C	-5
Boiling point	ASTM D 1120	°C	105

CONDITIONS DE STOCKAGE

This Glaciol coolant should be stored in a dry, well-ventilated area at a temperature between 5 °C and 30 °C, protected from direct sunlight.

Use properly sealed original containers and wear appropriate protective equipment during handling. A Safety Data Sheet (SDS) is available from the sales representative.



   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12