

BARAKA
TRANS

75W80
SYNTHETIC MANUAL TRANSMISSION OIL

HUILE DE TRANSMISSION

DESCRIPTION

BARAKATRANS 75W80 is a synthetic-based lubricant for manual and automated manual transmissions, whether synchronized or non-synchronized, operating under the most severe load, speed, and temperature conditions.

APPLICATION

BARAKATRANS 75W80 is particularly suitable for extended drain intervals in gearboxes of commercial vehicles from Renault Trucks, DAF, and Iveco, as well as all commercial vehicles equipped with reduction gearboxes and any application requiring an **API GL-4** performance level.

SPECIFICATIONS

- API GL-4
- MB-Approval 235.29
- ZF TE-ML 01E / 02E / 16P
- VOLVO 97307
- MAN 341 Type Z5
- MAN 341 Type VR

AVAILABILITY



Available in: 1L / 200L drum

BARAKA
TRANS

75W80

SYNTHETIC MANUAL TRANSMISSION OIL

HUILE
-DE-TRANSMISSION

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Test	Unit	Results
GRADE		75W80
Density at 15 °C	-	0,853
Viscosity at 100 °C	mm ² /s	9.35
Viscosity at 40 °C	mm ² /s	54
Viscosity Index	-	157
Flash Point	C°	240
Pour Point	C°	-42

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

Pétro
Baraka

   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12