

BARAKA
TRANS

ATF 1200
AUTOMATIC TRANSMISSION FLUID



DESCRIPTION

BARAKATRANS HI GRUARD ATF 1200 Automatic Transmission Fluid (ATF) suitable for all systems requiring DEXRON or MERCON specifications. It is particularly recommended for automatic transmissions from: American manufacturers: GM, FORD, CHRYSLER Asian manufacturers: HYUNDAI, KIA, MITSUBISHI, TOYOTA European manufacturers: BMW, CITROËN, FIAT, MERCEDES, PEUGEOT, RENAULT Also suitable for older-generation automatic transmissions, torque converters, power steering systems, marine reversing gear systems, hydrostatic transmissions, hydraulic or mechanical systems where DEXRON or MERCON specifications are required

AVANTAGE CLIENT

- Excellent thermal and oxidation stability, preventing deposit formation
- Effective protection against wear and corrosion
- Good low-temperature flow and reliable lubricant film at high operating temperatures
- Superior friction performance

PERFORMANCE STANDARDS

- DEXRON IIIH
- FORD MERCON V
- ALLISON C4

OEM APPROVALS

- MB-Approval 236.9 DTFR 13C170

AVAILABILITY



Available in: 1L / 200L drum

BARAKA TRANS

ATF 1200

AUTOMATIC TRANSMISSION FLUID



RECOMMANDATION

Allison TES 295 • BMW 7045 E • BMW 8072 B • BMW LA 2634 • BMW LT 71141 • Caterpillar TO-2
Chrysler ATF +3 • JWS 3309 (Aisin Warner) • MAN 339 Typ V1 • MAN 339 Typ Z1 • MAN 339 Typ Z2
MB (Mercedes-Benz) 236.2 • 236.5 • 236.6 • 236.7 • 236.10 • 236.11 • 236.91 • Subaru ATF • Voith H55.6335
Volvo 97340 • Volvo 97341 • ZF TE-ML 03D • TE-ML 04D • TE-ML 05L • TE-ML 09 • TE-ML 14A • TE-ML 14B
TE-ML 17C • Honda ATF Z1 (sauf CVT) • Hyundai SP-II, SP-III • JASO 1-A • Mazda ATF M-III, M-V • Mitsubishi SP-II
SP-III • Nissan AT-Matic D Fluid • AT-Matic J Fluid • Toyota Type T-II • Type T-IV

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Name	Units	Results
Density at 15 °C	-	0,866
Viscosity at 100 °C	mm ² /s	7.3
Viscosity at 40 °C	mm ² /s	36
Viscosity Index	-	173
Flash Point	°C	208
Pour Point	°C	-45

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

**Pétro
Baraka**

   **PétroBaraka**
www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12