

BARAKA TRANS

75W90

SYNTHETIC MANUAL TRANSMISSION OIL

Ze Synergy

DESCRIPTION

BARAKA TRANS SYNERGY ZE 75W-90 is extremely shear-stable and ensures reliable retention of the SAE 75W-90 viscosity grade.

Its high additive reserve allows for extended drain intervals in accordance with manufacturer recommendations. Excellent low-temperature performance provides optimal wear protection, contributing to reduced fuel consumption, even during short trips and at low operating temperatures.

PERFORMANCES

PRODUCT PERFORMANCE LEVELS

- API GL-4 / GL-5 / MT-1

PERFORMANCES / OEM REQUIREMENTS

- ZF TE -ML 02B/05A/07A/12L/12N/16F/17B/19C/21A
- ROBERT BOSCH TE -ML 08
- ARVIN MERITOR 0-76-N
- SCANIA STO 1 :0/2:0 A FS
- MAN 341-Z2/341-E3 /342-S1
- MACK GO-J
- VOLVO 97312

OEM approvals:

- MB-Approval 235.8 DTFR 12B140 **NEW**

CLIENT BENEFITS

- Excellent lubricant stability under high-load operating conditions
- Outstanding corrosion protection and good compatibility with non-ferrous metals
- Excellent oxidation resistance
- Effective dispersion of suspended dust particles, ensuring component cleanliness even during extended drain intervals
- Very good compatibility with elastomers, helping to prevent leaks

AVAILABILITY



Available in: 1L / 200L drum

BARAKA TRANS

75W90

SYNTHETIC MANUAL TRANSMISSION OIL

Les Synergy

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Test	Unit	Results
GRADE		75W90
Density at 15 °C	-	0,871
Viscosity at 100 °C	mm ² /s	15.67
Viscosity at 40 °C	mm ² /s	105,29
Viscosity Index	-	158
Flash Point	C°	204
Pour Point	C°	-52

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

**Pétro
Baraka**

   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12