

BARAKA
TRANS

ATF 1800
AUTOMATIC TRANSMISSION FLUID

X-Drive

DESCRIPTION

BARAKATRANS X-DRIVE ATF 1800 High-technology lubricant for new generation automatic gearboxes, formulated from synthetic base oils and modern high-performance additives. It is designed to meet the most stringent requirements of automotive manufacturers. This fluid ensures optimal wear protection, excellent transmission cleanliness, as well as a fluid and precise gear shift response, even at low temperatures. It also guarantees optimal friction behavior and exceptional aging resistance, thanks to the use of virgin base oil.

- **This fluid ensures optimal wear protection, excellent transmission cleanliness, as well as a fluid and precise gear shift response, even at low temperatures. It also guarantees optimal friction behavior and exceptional aging resistance, thanks to the use of virgin base oil.**

APPLICATION

➤ APPLICATION:

Designed for modern automatic transmissions

This oil offers increased energy efficiency and a notable reduction in mechanical losses thanks to its low viscosity. It maintains its lubricating properties over a wide temperature range and ensures reliable protection against wear, corrosion, and deposit formation.

PERFORMANCE

- **Dexron VI**
- **Ford Mercon LV**

CUSTOMER BENEFITS

- Excellent thermal and oxidation stability, preventing deposit formation.
- Effective protection against wear and corrosion.
- Favorable flow properties and reliable lubricant film consistency at high operating temperatures.

BARAKA TRANS

ATF 1800

AUTOMATIC TRANSMISSION FLUID

X-Drive

SAFETY MEASURES



Flammable product :

Do not breathe in; wear personal protective equipment (gloves, masks, etc.) and ventilate the workspace.

RECOMMANDATION

- Aisin Warner AW-1 • BMW 83 22 0 142 516 • BMW 83 22 2 152 426 • BMW 83 22 2 289 720 • BMW 83 22 2305 396 • BMW 83 22 2 305 397 • BMW 83 22 2 355 599 • BMW M-1375.4 • Dexron VI • Fiat 9.55550-AV5
- Ford Mercon LV • Honda ATF 3.1 • Honda DW-1 • Honda Typ 3.0 • Hyundai SP-III • HYundai SP-IV
- Hyundai SP-IV-RR • Isuzu ATF WSI • JASO 1A-LV • JWS 3324 (AisinWarner) • Land Rover TYK 500050
- Mazda ATF FZ • MB-Approval 236.12 • MB-Approval 236.14 • Mitsubishi Dia Queen ATF-MA1
- Mitsubishi Dia Queen ATF-PA • Nissan ATF-Matic S Fluid • Nissan Matic P • Toyota WS • VW G 055 005
- VW G 055 162 • VW G 055 540 • VW G 060 162"

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Name	Test Methods	Units	Results
Density at 15 °C	ASTM D 4052	-	0.85146
Viscosity at 100 °C	ASTM D 445	mm ² /s	28.16
Viscosity at 40 °C	ASTM D 445	mm ² /s	5.75
Viscosity Index	ASTM D 2270	-	152
Flash Point	ASTM D 97	°C	-48
Pour Point	ASTM D 92	°C	>210

BARAKA TRANS

ATF 1800

AUTOMATIC TRANSMISSION FLUID

X-Drive

TYPICAL CHARACTERISTIC

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

AVAILABILITY



Available in: 1L / 200L drum



Péto Baraka

   **PétoBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12