

COMPRESS AIR

46

DESCRIPTION

COMPRESS AIR 46 : is a high-quality lubricant specifically formulated for the lubrication of high-pressure air compressors.

APPLICATION

- Lubrication and cooling of air compressors, including:
 - **Rotary screw compressors**
 - **Reciprocating (piston) compressors**
- **Recommended for the lubrication of ball bearings, anti-friction bearings, and industrial gears operating under severe service conditions**

SPECIFICATIONS

- **DIN 51506 VDL**

CLIENT BENEFITS

- Complete corrosion inhibition, ensuring protection even under humid operating conditions
- High flash point for enhanced operational safety
- Prevents the formation of carbon deposits on compressor valves

COMPRESS AIR

46

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

CHARACTERISTICS	Units	Typical
Grade	-	ISO VG 46
Density at 15°C	-	0,855
Viscosity at 40°C (KV40)	cSt	47,31
Viscosity at 100°C (KV100)	cSt	7,11
Viscosity index (VI)	-	108,39
Pour point (PP)	C°	-22
Flash point	C°	234

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

**Pétro
Baraka** 

   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12