

Péto
Baraka
LUBRIFIANT



MAGIC EP2 COMPLEXE

Graisse sulfonate de calcium
Ultra résistante



Graisse 

PERFORMANCE

CONFORME À LA NORME 

ISO 6743-9: L-XBEB 2

RÉPOND À LA NORME DIN 51502: KP2P-20

NLG2

UTILISATION

APPLICATIONS INDUSTRIELLES

APPLICATIONS AGRICOLES 

TRANSPORT ROUTIER 

APPLICATIONS SPÉCIALISÉES 



GRAISSE
SULFONATE DE CALCIUM
ULTRA
RÉSISTANTE

”حكاية ثقة..”

MAGIC Graisse sulfonate
de calcium
Ultra résistante

COMPLEXE EP2



**MULTI-USAGE
PROFESSIONNEL**

DESCRIPTION

La graisse MAGIC COMPLEXE EP2 a calcium sulfonate complex soap grease, is a high-performance lubrication solution designed to meet the most demanding requirements in terms of efficiency and mechanical protection. It is formulated from carefully refined mineral base oils and a calcium sulfonate complex thickener.

The exceptional properties of MAGIC COMPLEXE EP2 result from the nature of its thickening agent, which provides outstanding resistance to corrosion and extreme pressure. In addition, carefully selected additives ensure excellent oxidation resistance, enhancing stability during severe mechanical applications.

APPLICATION

MAGIC COMPLEXE EP2 is specifically recommended for the lubrication of automotive and industrial applications operating under harsh conditions. It is particularly well suited for high-speed applications where conventional calcium sulfonate soap greases prove insufficient.

MAGIC COMPLEXE EP2 is a multipurpose grease formulated for the lubrication of various components such as wheel bearings, ball bearings, plain bearings, roller bearings, standard seals, and subjected to high loads. It also provides optimal performance in applications exposed to shock loads and vibrations, including transport, agricultural, and off-road vehicle operations.

MAGIC COMPLEXE EP2 is the ideal solution for industrial applications requiring an extreme-pressure, high-temperature grease of NLGI grade 2.

SPECIFICATIONS

- Complies with ISO 6743-9: L-XBEHB 2
- Meets DIN 51502: KP2P-20
- NLGI 2

MAGIC Graisse sulfonate
de calcium
Ultra résistante

COMPLEXE EP2





**MULTI-USAGE
PROFESSIONNEL**

CLIENT BENEFITS

- Meets the requirements of major automotive manufacturers and equipment, ensuring broad compatibility.
- Superior cold temperature flow properties allow use in extreme environments, even at low temperatures.
- Excellent adhesion provides outstanding resistance to water washout and water spray, ensuring optimal protection in wet conditions.

TYPICAL CHARACTERISTIC

MAGIC COMPLEXE EP2 is the preferred versatile, high-performance grease for ensuring reliable lubrication and protection of mechanical equipment operating under severe conditions.

Name	Test Methods	Units	Results
Thickener	SAE J300	-	Sulfonate de calcium
NLGI Grade	ASTM D 217/DIN 51 818	-	2
Color	 Visual	-	Marron foncé
Appearance	 Visual	-	Lisse
Operating temperature range	-	°C	-20 à 180
Penetration at 25°C	ASTM D 217/DIN51 818	0,1mm	265 - 295
4-Ball weld test	ASTM D 2266	mm	0.36
Base oil kinematic viscosity at 40°C	ASTM D 4069	%	20
Dropping point	ASTM D 566	°C	250

MAGIC Graisse sulfonate
de calcium
Ultra résistante

COMPLEXE EP2

**MULTI-USAGE
PROFESSIONNEL**



STORAGE CONDITIONS

To preserve product quality and performance, please observe the following storage conditions:

- **Température:** Do not store products at temperatures above 60 °C. Store in a cool, dry environment to prevent degradation.
- **Sunlight protection:** Avoid direct exposure to sunlight, as this may alter the chemical composition and reduce effectiveness.
- **Extreme temperatures:** Avoid storage in areas subject to extreme cold or significant temperature fluctuations, which may affect product stability.
- **Weather protection:** Whenever possible, do not expose packaging to weather conditions such as rain or snow. If exposure is unavoidable, drums should be stored horizontally to prevent water contamination and preserve label integrity for clear product identification.

By strictly following these storage guidelines, you will ensure extended service life and optimal use of the product.

**Pétro
Baraka**

PétroBaraka
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12