

Péto
Baraka
LUBRIFIANT



PERFORMANCE MINÉRAL



PERFORMANCE

CONFORME À LA NORME
API SF/CF



UTILISATION

APPLICATIONS INDUSTRIELLES
TRANSPORT ROUTIER 
4X4 ET UTILITAIRES ANCIENS
VÉHICULES À MOTEUR ESSENCE OU DIESEL NON TURBO



GAMME
SYNTHÉTIQUE
CLASSIC

”حكاية ثقة..”

PERFORMANCE MINÉRAL

SAE 20W50

MINERAL
MULTIGRADE OIL



DESCRIPTION

PERFORMANCE PB-3100 20W50 : Multigrade mineral detergent oil, specially additized for the lubrication of gasoline and diesel engines, whether turbocharged or not, for passenger vehicles used under normal service conditions.

APPLICATION

PERFORMANCE PB-3100 20W50 : was developed to meet the most demanding requirements of gasoline and diesel engines (passenger cars and light commercial vehicles).

PERFORMANCE PB-3100 20W50 : is particularly suitable for turbocharged engines. This engine oil is perfectly adapted for vehicles equipped with catalytic converters and using unleaded fuel or liquefied petroleum gas.

PERFORMANCE PB-3100 20W50 : can be used under all driving conditions (urban traffic, roads, highways) and in any season.

PERFORMANCES :
Normes Internationales

- API SF/CF

CUSTOMER BENEFITS

- Very good viscosity stability in service.
- Excellent antioxidant, anti-rust, and anti-foam properties.
- **Viscosité : PERFORMANCE PB-3100 20W50** has a high viscosity index and excellent viscosity stability..

PERFORMANCE MINÉRAL

SAE 20W50

MINERAL
MULTIGRADE OIL



TYPICAL FEATURE

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics while ensuring the product remains in compliance with its specifications.

Test	Units	Test Methods	Result
SAE Viscosity Grade	SAE J300	-	20W50
Densité à 15 °C	ASTM D 4052	-	0,879
Kinematic Viscosity at 40°C	ASTM D 445	mm ² /s	162.21
Kinematic Viscosity at 100°C	ASTM D 445	mm ² /s	18.28
Viscosity Index	ASTM D 2270	-	126
Pour Point	ASTM D 97	°C	-30
Flash Point	ASTM D 92	°C	>200
TBN	ASTM D 2896	(mg KOH/g)	6.32

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

Péto
Baraka

   **PétoBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12