

PERFORMANCE

PB-7100

SAE 10W40

SEMI-SYNT



DESCRIPTION

PERFORMANCE PB-7100 10W40: is a high-performance semi-synthetic oil specially developed for diesel and gasoline engines of passenger or utility vehicles to ensure maximum engine cleanliness in all weather conditions.

APPLICATION

PERFORMANCE PB-7100 10W40 : Suitable for engines equipped with catalytic converters. Also suitable for any engine using unleaded fuel, diesel, LPG.

- **Recommended for passenger car diesel engines.**
- **This product can be used with direct injection or older diesel engines.**

PERFORMANCES :

- **International Standards**
- **ACEA A3/ B3- A3/B4**
- **API SL/CF**

APPROVALS :

- **MB-Approval 229.3**
- **PSA B71 2300**
- **VW 501 01/ 505 00**

CLIENT BENEFITS

- Provides protection in tough operating conditions where longer intervals between oil changes are recommended, reducing maintenance costs.

PERFORMANCE

PB-7100

SAE 10W40
SEMI-SYNT



AVANTAGES CLIENT

➤ Performance over a wide range of temperatures, viscosity and thermal stability ensures protection at high temperatures and fluidity at low temperatures.

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Petro Baraka reserves the right to modify certain characteristics in accordance with a conformity of the product its specifications.

Test parametres	ASTM Method	Unit	Value
Viscosity grade SAE	SAE J300	-	10W40
Density at 15°C	ASTM D 4052	kg/m ³	866
Kinematic viscosity at 40 °C	ASTM D 445	mm ² /s	98.9
Kinematic viscosity at 100°C	ASTM D 445	mm ² /s	14.7
Viscosity index	ASTM D 2270	-	155
Pour Point	ASTM D 97	°C	-35
Flash Point	ASTM D 92	°C	>200
Total Base Number, TBN	ASTM D 2896	(mg KOH/g)	9

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations.

If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

