

Péto
Baraka
LUBRIFIANT



PERFORMANCE

SAE 5W40

SYNT



Huile moteur 

PERFORMANCE

NORMES INTERNATIONALE
ACEA A3/B4
API SN



HOMOLOGATION

- MB-APPROVAL 229.5
- VW 502 00/ 505 00
- RN 0700/0710
- PSA B71 2296



GAMME
SYNTHÉTIQUE
CLASSIC

”حكاية ثقة..”

PERFORMANCE

PB-9100

SAE 5W40
SYNT



DESCRIPTION

PERFORMANCE SYNT PB-9100 5W40 : It is a 100% synthetic oil designed for high-performance gasoline, diesel, and LPG engines. It has numerous manufacturer approvals for use in powerful, highly-stressed engines, including gasoline/LPG multi-valve, turbocharged or naturally aspirated engines, as well as direct injection diesel engines.

USAGE

PERFORMANCE SYNT PB-9100 5W40 : This product is approved by major automobile manufacturers. In all cases, it is recommended to check the manufacturer's specifications in the vehicle maintenance manual.

PERFORMANCES :

- Normes Internationales
- ACEA A3 / B4
- API SN

Homologations :

- MB-Approval 229.5
- VW 502 00/ 505 00
- RN 0700/ 0710
- PSA B71 2296

CUSTOMER BENEFITS

- Excellent oxidation resistance ensures the preservation of lubrication properties even during extended oil change intervals
- Strong cold-weather performance provides reliable engine protection from the moment of startup.
- Optimized anti-wear properties help extend the engine's lifespan.

PERFORMANCE

PB-9100

SAE 5W40
SYNT



TYPICAL CHARACTERISTICS

These values are typical of the current production. However, Petro Baraka reserves the right to modify certain characteristics to ensure the product remains compliant with its specifications.

Nom	Methodes d'essai	Unites	Résultats
Viscosity Grade (SAE)	SAE J300	-	5W40
Density at 15°C	ASTM D 4052	-	0,854
Kinematic Viscosity at 40°C	ASTM D 445	mm ² /s	84.63
Kinematic Viscosity at 100°C	ASTM D 445	mm ² /s	14.10
Viscosity Index	ASTM D 2270	-	173
Pour Point	ASTM D 97	°C	-39
Flash Point	ASTM D 92	°C	>200
Total Base Number (TBN)	ASTM D 2896	(mg KOH/g)	11

STORAGE CONDITIONS

Do not store products at temperatures exceeding 60°C. They should be kept away from sunlight, extreme cold, and external temperature fluctuations.

Whenever possible, packaging should not be exposed to adverse weather conditions. If unavoidable, drums must be stored horizontally to prevent water contamination and to preserve the product label.

**Pétro
Baraka**

   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12