

PERFORMANCE

PB-9300

SAE 5W30
ULTRA



DESCRIPTION

ULTRA PERFORMANCE PB-9300 5W30 : is a 100% synthetic oil classified in the group III for light gasoline and diesel engines of the latest generation, it is characterized by its high fuel economy capacity.

Specially designed for new engines of Mercedes Benz and Volkswagen, recommended for all types of use and in particular in severe conditions.

APPLICATION

PERFORMANCE ULTRA PB-9300 5W30 : Synthetic anti-pollution technology engine lubricant offers the best engine protection against wear and fouling.

PERFORMANCE ULTRA PB-9300 5W30 : is compatible with light commercial diesel vehicles and petrol and diesel passenger cars. This specially formulated low viscosity, low friction oil this specially formulated low-viscosity, low-friction oil extends oil change intervals.

Before using the product, it is important to check the vehicle maintenance manual: oil changes are carried out in accordance with the manufacturer's recommendations.

PERFORMANCES :

- International Standards
- **ACEA** C2 / C3
- **API** SN

APPROVALS :

- **MB-Approval** 229.52
- **VW** 505 00/ 505 01
- **Meets Fiat** 9.55535-S1
- **Meets Fiat** 9.55535-S3

PERFORMANCE

PB-9300

SAE 5W30
ULTRA



CLIENT BENEFITS

- Optimizes fuel economy and high-performance engine to protect against wear, this helps extend the engine's life.
- Formulated for rapid circulation during cold starts at low temperatures, which protection against engine wear.

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Petro Baraka reserves the right to modify certain characteristics in accordance with a conformity of the product its specifications.

Test parametres	ASTM Method	Unit	Value
Viscosity Grade SAE	SAE J300	-	5W30
Density at 15°C	ASTM D 4052	kg/m ³	851
Kinematic viscosity at 40 °C	ASTM D 445	mm ² /s	71.51
Kinematic viscosity at 100°C	ASTM D 445	mm ² /s	12.11
Viscosity Index	ASTM D 2270	°C	167
Pour point	ASTM D 97	°C	-40
Flash Point	ASTM D 92	°C	>200
Total Base Number, TBN	ASTM D 2896	(mg KOH/g)	7

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations.

If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

