

ULTIMA

HUILE MINÉRAL
Monograde

S10W

MINÉRAL

DESCRIPTION

ULTIMA S10W is a monograde hydraulic oil for heavy-duty systems, formulated to meet CATERPILLAR TO-2 requirements. It is made from highly refined paraffinic base oils and advanced additive technology.

APPLICATIONS

ULTIMA S10W : is a high-performance hydraulic oil specifically designed for vehicles and equipment operating under intensive conditions across a wide range of climates and ambient temperatures. SAE 10W high-performance hydraulic oil is generally recommended for Caterpillar machinery.

PERFORMANCES :
INTERNATIONAL STANDARDS

- ALLISON C-4
- CATARPLAR TO-2

CLIENT BENEFITS

- Long service life due to excellent thermal and chemical stability of the lubricant film
- High air-release capacity and outstanding anti-foam performance

ULTIMA

HUILE MINÉRAL
Monograde

S10W

MINÉRAL

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Name	Test Methods	Units	Results
SAE Viscosity Grade	SAE J300	-	S10W
Density at 15 °C	ASTM D 4052	-	0,867
Kinematic Viscosity at 40 °C	ASTM D 445	mm ² /s	34.38
Kinematic Viscosity at 100 °C	ASTM D 445	mm ² /s	5.65
Viscosity Index	ASTM D 2270	-	102
Pour Point	ASTM D 97	°C	-27
Flash Point	ASTM D 92	°C	220

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

**Pétro
Baraka**

   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12