

ULTIMA

Oil MINÉRAL
Monograde

SAE 30

DESCRIPTION

ULTIMA SAE 30 is a mineral lubricant recommended for fleets of older diesel engines used in transportation, certain public works equipment, construction machinery, mining operations, and agricultural vehicles. It is also suitable for stationary engines.

APPLICATION

ULTIMA SAE 30 can be used in all types of engines where a monograde **SAE 30** lubricant is recommended

SPECIFICATIONS

PERFORMANCES :
International Specifications

- **API SF/CF**

CLIENT BENEFITS

- Good oxidation resistance, preventing the formation of deposits and varnish on components operating at high temperatures.
- A balanced combination of detergent, dispersant, and anti-wear additives, effectively combating engine contamination.
- Effective control of soot, sludge, and piston deposits, ensuring optimal engine performance.

ULTIMA

Oil MINÉRAL
Monograde

SAE 30

TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Property	Test Methods	Units	Results
SAE Viscosity Grade	SAE J300	-	SAE 30
Density at 15 °C	ASTM D4052	-	0,885
Kinematic Viscosity at 40 °C	ASTM D445	mm ² /s	96,2
Kinematic Viscosity at 100 °C	ASTM D445	mm ² /s	11
Viscosity Index	ASTM D2270	-	99
Pour Point	ASTM D97	°C	-20
Flash Point	ASTM D92	°C	>220
TBN	ASTM D2896	(mgKOH/g)	6,4

STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

**Pétro
Baraka**

   **PétroBaraka**
 www.petrobaraka.com
contact@petrobaraka.com



رمز الثقة
SYMBOLE DE CONFIANCE
منتج وموزع من طرف شركة ذ م م بيترو بركة
Oued zmor, la route nationale n46 Lot n01, Biskra
+213 (0) 33 55 27 11, 12