

# ULTIMA

Oil MINÉRAL  
Monograde

## SAE 50

### DESCRIPTION

**Ultima SAE 50** is a high-performance monograde engine oil designed for diesel and gasoline engines (including Detroit Diesel) operating in both on-road and off-road applications. Formulated with proven high-quality base oils, it is engineered to meet the specific lubrication requirements of this type of engine and incorporates detergent additives.

### APPLICATION

**Ultima SAE 50** : is recommended for older diesel and gasoline engines used in agricultural machinery, construction equipment, marine equipment, and other off-road applications where the manufacturer specifies an SAE 50 viscosity grade.

**Ultima SAE 50** : It uses reliable technology to ensure consistent performance in older engines operating on very low sulfur diesel fuels.

### PERFORMANCES :

Specifications Internationales

- API SF/CF

### CLIENT BENEFITS

- Excellent oxidation resistance, preventing the formation of deposits and varnish on components operating at high temperatures.
- A balanced combination of detergent, dispersant, and anti-wear additives, effectively combating engine contamination.
- Effective control of soot, sludge, and piston deposits, ensuring optimal engine operation.

# ULTIMA

Oil MINÉRAL  
Monograde

## SAE 50

## TYPICAL CHARACTERISTIC

These values are typical of current production. However, Pétro Baraka reserves the right to modify certain characteristics in accordance with the product's conformity to its specifications.

Property	Test Methods	Units	Results
SAE Viscosity Grade	SAE J300	-	SAE 50
Density at 15 °C	ASTM D4052	-	0,885
Kinematic Viscosity at 40 °C	ASTM D445	mm <sup>2</sup> /s	96,2
Kinematic Viscosity at 100 °C	ASTM D445	mm <sup>2</sup> /s	11
Viscosity Index	ASTM D2270	-	99
Pour Point	ASTM D97	°C	-20
Flash Point	ASTM D92	°C	>220
TBN	ASTM D2896	(mgKOH/g)	6,4

## STORAGE CONDITIONS

Do not store products at temperatures above 60°C. It must be stored away from direct sunlight, intense cold and external temperature fluctuations. If possible, the packaging should never be exposed to weather. Otherwise, the drums shall be placed horizontally, so as to avoid contamination by water and to preserve the product label.

**Pétro  
Baraka**

   **PétroBaraka**  
 [www.petrobaraka.com](http://www.petrobaraka.com)  
[contact@petrobaraka.com](mailto:contact@petrobaraka.com)



**رمز الثقة**  
**SYMBOLE DE CONFIANCE**  
منتج وموزع من طرف شركة ذ م م بيترو بركة  
Oued zmor, la route nationale n46 Lot n01, Biskra  
+213 (0) 33 55 27 11, 12